(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 28 July 2005 (28.07.2005)

PCT

(10) International Publication Number WO 2005/068838 A1

(51) International Patent Classification7: 15/04

F04C 2/344.

(21) International Application Number:

PCT/EP2005/050037

- (22) International Filing Date: 5 January 2005 (05.01.2005)
- (25) Filing Language:

English

(26) Publication Language:

English

- (30) Priority Data:
 - BO2004A000008
- 9 January 2004 (09.01.2004) IT
- (71) Applicant (for all designated States except US): PIER-BURG S.p.A. [IT/IT]; Zona Industriale Contrada Cerratina, I-66034 LANCIANO (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): ARMENIO, Giacomo [IT/IT]; Via S. Lucia, 10, I-57128 LIVORNO (IT). CELATA, Bernardo [IT/IT]; Via Goito, 34, I-57100 LIVORNO (IT).
- (74) Agents: JORIO, Paolo et al.; STUDIO TORTA S.r.l., Via Viotti, 9, I-10121 TORINO (IT).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, 7.W.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

[Continued on next page]

(54) Title: PUMPING SYSTEM



(22) a pressure (p2) lower than the pressure of a second chamber (20). The system (100*) is characterized in that the first control chamber (22) of the pump (10*) has a channel (40) connecting the first control chamber to an oil inlet (23). And the channel (40) has an opening/closing device (41) controlled selectively by an engine operating parameter, such as oil temperature.

WO 2005/068838 A1

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.